PJ358

LIGHT, BRIGHT AND PORTABLE PROJECTOR

WITH KEYSTONE CORRECTION

Versatile and highly portable.

The ViewSonic® PJ358 ultra-portable projector is a performance leader with a rich feature set at an affordable price. The PJ358 delivers 2,000 LUMENS AND 1024X768 XGA RESOLUTION for crisp, detailed images in any lighting situation. The short throw distance enables you to DISPLAY A 60-INCH IMAGE FROM 4.9 FEET. At just 3.9 lbs, This projector's portability is enhanced by its small footprint. It's also easy to set up with auto vertical keystone correction and easy to pack up with its DIRECT OFF FEATURE. A wide array of PC and video connectivity options let you deliver dynamic, versatile presentations and you can connect a USB FLASH DRIVE to project JPEG and M-JPEG images without a PC. The PJ358 is ideal for table-top or mounted use in the office or on the road.

DYNAMIC MEETINGS AND PRESENTATIONS

- **Bright in virtually any setting with 2,000 lumens**
  Packs 2,000 lumens in just 3.9 lbs. It's the bright choice for mobile presenters.
- **Quick set up**
  Auto vertical keystone correction automatically squares the image for quick set up. The direct off feature lets you just unplug the projector and go.
- **Present without PC**
  USB flash drive lets you project JPEG and M-JPEG images without a PC.
- **Enhanced security features**
  Assign a PIN code to password protect the projector from unauthorized use.
- **Ultimate display source flexibility**
  Connect a computer (2 RGB inputs) or add a video source for dynamic meetings and presentations.
- **Easy maintenance**
  The sliding filter cover and simple lamp replacement from the top of the unit make maintenance a breeze.
- **Whisper-mode extends lamp life and reduces noise output**
- **The best warranty in the business**

MORE THAN 2000 AWARDS

VIEWSONIC
PRODUCTS, PROGRAMS, AND SERVICES

ViewSonic®
See the difference®

PJ358

LIGHT, BRIGHT AND PORTABLE PROJECTOR WITH KEYSTONE CORRECTION

PROJECTOR	Type	0.6" Poly-Si TFT with micro-lens
	Pixel Format	1024x768 XGA
	Lens	Manual zoom, manual focus
	Zoom Factor	1.2
	Keystone	Vertical ± 30°
DISPLAY	Size	30"–300" (diagonally)
	Throw Distance	32"–307"
	Throw Ratio	1.3-1.5:1
	Lamp	160W, 2,000 hours normal, up to 3000 hours whisper**
	Brightness (max)	2,000 ANSI lumens
	Contrast Ratio	500:1
	Aspect Ratio	4:3 (native), 16:9
AUDIO	Speakers	1x1 watts
INPUT SIGNAL	Video	RGB analog, NTSC M, NTSC 4.43, PAL, SECAM, HDTV (480i, 480p, 576i, 720p, 1080i)
	Frequency	F_h: 31–106kHz; F_v: 56–120Hz
COMPATIBILITY	PC	Analog: from VGA up to UXGA (scaled)
	Mac®†	Analog: up to SXGA (may require a Mac adapter)
CONNECTOR	RGB (input)	15-pin HD, D-sub cable (x2)
	Composite Video (input)	RCA jack (x1)
	S-Video (input)	Mini-Din 4-pin
	Component Video (input)	VGA DB-15 to component adapter*
	Audio (input/output)	Stereo mini-jack 1 in, 1 out
USB		Type A(x1) for PC-less presentation (JPEG, M-JPEG) Type B(x1) for mouse control
POWER	Voltage	100–240 VAC, 50–60Hz (universal)
	Consumption	250W (typ)
CONTROLS	Basic	Standby, input, reset, V keystone
	OnView®	Language, brightness, contrast, gamma, color temperature, color, tint, sharpness, progressive, My Memory, aspect, overscan, V. position, H. position, H. phase, H. size, auto adjust, color space, component, video format, information, V. keystone, whisper, mirror, volume, language, menu position, OSD bright, blank color, start up, My Screen, My Screen Lock, message, auto search, lamp time, filter time, service menu, security, USB storage
OPERATING CONDITIONS	Temperature	41–95°F (5–35°C)
	Humidity	10–85% (non-condensing)
NOISE LEVEL	Normal	36 dB (typ)
	Whisper Mode	30 dB (typ)
DIMENSIONS (W x H x D)	Physical (mm)	274mm x 205mm x 59mm
	Physical (in.)	10.8" x 8.1" x 2.3"
WEIGHT	Net	3.9 lb. (1.8 kg)
	Gross	9.9 lb. (4.5 kg)
REGULATIONS		UL 60950, C-UL, FCC-B, UL-DEMKO/GS, CCC, CB, CE, C-TICK, GOST, NOM, PSB, TUV-S
OTHER		Short throw, auto vertical digital keystone correction, progressive scan, 3:2 pull down, auto adjust, remote control, direct off, low noise (30 dB), unplug and go, daylight mode, adjustable fan speed
WARRANTY		Three-year limited warranty on parts and labor, first-year Express Exchange® Service. One-year limited warranty on lamp***

Optional Accessories

- Replacement lamp RLC-027
- Extended Express Exchange® PRJ-EE-05-03
- Soft case with wheels and laptop bag CASE-006
- Universal ceiling mount kit WMK-005
- VGA to component video adapter . . .ADPT-002
- Wireless G Presentation Adapter WPG-100

ViewSonic® See the difference®

Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Optional cables required. **Running whisper-mode exclusively can extend lamp life. ***Visit ViewSonic.com for full details. †Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs vary by country. See your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2007 ViewSonic Corporation. All rights reserved. [13306-01B-11/07] PJ358-1